


8 CH

RS-N7708HR-P 8CH AI Network Video Recorder

Features:

- Supports upto 8MP, 256Mbps
- 1 Bay HDD upto 10TB
- Video Compression : H.264/H.265
- Supports Artificial Intelligence



Specifications

Video	Resolution	8MP,5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P)
Recording Bandwidth	Inputs	112M
	out	96M
Performance		
Live/Playback	Compression	Audio: G.711a Video : H.264/H.265
	Frame rate	4K:60fps 4MP:120fps 2MP:240fps
	AI	yes
	Event	MD(Sensitivity Level 1~8)
		Videlo loss
		Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x)
		Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 8CH playback
	Fisheye	Use WEB CMS,device does not support
UI/Monitoring	Local	UI5.0
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Mobile viewer	Rxcamview
	Push Notification	yes

Interface		
P/W Reset		Factory Reset : Press 10 seconds
Monitors	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
	HDMI 1	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
Connections	POE	8*RJ45、802.3at/af
	Ethernet	1 RJ45 100/1000 Base-T
	USB	USB2.0*1(front) USB2.0*1+(rear)
	Audio out	1
	E-sata	1 optional, not supported by default
	HDD	1 SATA, up to 10TB
	Line in	1 optional, not supported by default
	RS485	1 optional, not supported by default
	Alarm Input/out	8 in /no out optional, not supported by default
General		
OSD Language		English/French/Spanish/Portuguese/German/Italian/Greek/ Danish/Finnish/Russia/Hebrew/Turkish/Bulgarian/Arabic/Korean/Japanese/Thai/Hindi/Romanian/Dutch/Polish
Mechanical design	Dimension (WxDxH)	300X227X53mm
Electrical	Input Voltage/Current	1HDD:DC48V/1.2A 2HDD:DC48V/2A PoE Swith :48V
	Power consumption (excluding hard disk)	4W
Environmental	Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F) Humidity : Less than 90%RH